

**QC TRI PRO-5.5X**  
**QuietCool Trident Pro Line**

**QC TRI PRO-5.5X Specifications**

Air Flow	Hi: 5,068 CFM / Low: 4,438 CFM	
HVI-916 Airflow (for CA Title 24 New Construction)	Hi: 3,940 CFM / Low: 3,220 CFM	
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 1,689 SQFT to 2,534 SQFT	
Energy Use	Hi: 632 Watts / Low: 522 Watts	
Amps	Hi: 5.56 / Low: 4.53	
Motor Voltage	120 VAC, 60 Hz	
# of Speeds	2	
dBA	Hi: 51.2 / Low: 45.7	
Minimum Attic Clearance	38"	
Duct Diameter	20"	
Duct Length	9 feet	
Motor Head Diameter	20 1/2"	
Motor Head Length	13 1/2"	
Dampers	Barometric Pressurized R5 Dampers	
Controls (Sold Separately)	Included: 8 Hr Electronic Timer & HI-LOW-OFF switch Optional: IT-36002 QuietCool RF Wireless Control Kit	
Warranty	15 Years	
Framing	None Required	
Joist Cutting	None Required; fits 16" or 24" on center	
Minimum Suggested Attic Venting	6.76 SQ FT net free area	
Ceiling Rough Opening	14 1/4" x 30 1/4"	
Removable Grille Outside Dimension	16" x 32"	
Shipping Weight	75 lbs.	
Box Dimensions	39" x 24" x 39"	
In The Box	-QC TRI PRO-5.5X Motorhead -Ceiling Grille -Cut-out Template -Window Locks	-Damper Box -9 Foot Duct -Accessory Bag -Controls



For more information, visit our website at:  
[QUIETCOOLSYSTEMS.COM](http://QUIETCOOLSYSTEMS.COM)