



PRO1 SUBMITTAL SHEET

Job Name: _____ Location: _____ Date: _____

Purchaser: _____ Installer: _____

Submitted to: _____ For: RNC R&R Commercial

MODEL T771

Single Stage

1 Heat Only or 1 Cool Only

Battery or Hardwire

Non-Programmable



This model features:

- 4 sq. inch display
- Blue backlight
- Glow in the dark light button
- Easy access battery compartment
- Universal subbase
- Simple private label badge system
- Setpoint range from 25°F to 99°F (low set point is great for garage applications)
- Set point limits (meets building codes for garage applications)
- Mounts on wall or junction box
- 5 Year Warranty
- Customizable staging logic
- Heating and cooling swing (cycle rate) adjustments
- Battery or 24V power
- Room temperature calibration adjustments
- Easy wire color coded terminal blocks

Specifications:

Application	1 Heat Only or 2 Cool Only
Programmability	Non-Programmable
System Switch	Cool - Off - Heat - Auto
Display Range	20°F to 99°F (-7°C to 37°C)
Control Range	25°F to 99°F (-4°C to 37°C)
Display Accuracy	+/- 1°F
Heat Swing	Adjustable from 0.2°F to 2.0°F
Cool Swing	Adjustable from 0.2°F to 2.0°F
Terminals	Rc, Rh, C, G, Y/W
Load Rating	1 amp per terminal, 1.5 amp maximum all terminals combined
Power Source	18 to 30 VAC, NEC Class II, 50/60 Hz for hardwire (common wire) Battery power from 2 AA Alkaline batteries
Operating Ambient	20°F to +105°F (-7°C to +41°C)
Operating Humidity	90% non-condensing maximum
Mounting	Wall or Junction Box
Dimensions	4.7"W x 4.4"H x 0.8"D (119mm W x 112mm H x 20mm D)
Warranty	5 year warranty