



HM750A1000

ADVANCED ELECTRODE STEAM HUMIDIFIER

SUBMITTAL SHEET

Job Name	
Engineer	
Mechanical Contractor	
Contractor's P.O. No.	
Representative	
Notes	

Model(s)			
	Qty.	Notes	
	Qty.	Notes	
Approval			
Service			
Tag No.			



APPLICATION

The HM750 is the most advanced residential steam humidifier available and provides steady and reliable humidification for a home. The humidifier is designed for connection directly to a supply air duct for humidity on demand. The humidifier may be directly mounted to the air duct, or remotely from the air duct, with a steam hose connecting the humidifier to a distributor nozzle installed at the air duct.

INCLUDED IN THE BOX

- HM750 steam humidifier
- H6062 HumidiPRO
- Steam distributor nozzle
- Rubber drain hose
- LDPE water hose
- Baffle (duct mount only)
- Foam gasket (duct mount only)
- Steam hose (wall mount only)
- Fittings, hardware, and mounting template

SPECIFICATIONS

Operating Ambient Temperature: 41 to 104 °F (5 to 40 °C)

Power Supply:
120 VAC or 240 VAC
50/60 Hz

Power Consumption:
1.5 KW on 120 VAC
3.0 KW on 240 VAC

Amps: 12 A

Phase: 1

Circuit Breaker Max Current: 15 A

Steam Output:

On 120 VAC:
3.85 lb/hr
(1.75 kg/hr)
11 GPD

On 240 VAC:
7.7 lb/hr
(3.5 kg/hr)
22 GPD

Max Static Pressure:

2 in. w.c. positive backpressure
3 in. w.c. negative backpressure

Size (length x width x depth):

18 x 10 x 7 in.
457 x 254 x 178 mm

Weight:

10 lbs. (15 lbs. when full)
4.5 kg. (7.0 kg. when full)

By using this Resideo literature, you agree that Resideo will have no liability for any damages arising out of your use or modification to, the literature. You will defend and indemnify Resideo, its affiliates and subsidiaries, from and against any liability, cost, or damages, including attorneys' fees, arising out of, or resulting from, any modification to the literature by you.