VRF Controls and Accessories TCB-TC41U-UL—Remote Sensor

Submittal Data	
ob Name	Location
ag	
TOSHIBA	
Carrier	
	 SMMSi / SHRMi VRF Remote Sensor Features Prevents over-cooling or over-heating of the space
	· · · · · · · · · · · · · · · · · · ·
REMOTE SENSOR	
REMOTE SENSOR	
itttt	

TOSHIBA *Carrier*

PART NAME		TOUCH SCREEN CONTROLLER
Model Number		TCB-TC41U-UL
Power Supply (Rated Voltage)		7-19 VDC \pm 5% (No external power is required when CN61 is used)
Dimensions (H x W x D)	Inches	4.72 x 2.76 x 0.71
Weight (Touch Screen Controller)	Lbs	0.192
No. of Connected Units	•	1 to 16 units for 1 interface (Group connection for 2 or more connected units)

© 2024 Carrier. All rights reserved. Edition Date: 03/24 Form No: TCB-TC41U-UL Printed in U.S.A. Replaces: TCB-TC41L-UL

Manufacturer reserves the right to discontinue, or change at any time, specifications or designs without notice and without incurring obligations.

DIMENSIONAL DRAWING REMOTE SENSOR TCB-TC41U-UL

