

|   | 1492-WM3                            |                           |              |                     | 1492-WM4                            |                           |              |                     | 1492-WMD1                         |            |                           |
|---|-------------------------------------|---------------------------|--------------|---------------------|-------------------------------------|---------------------------|--------------|---------------------|-----------------------------------|------------|---------------------------|
| Dimensions are not intended to be used for manufacturing purposes.<br>Note: Height dimension is measured from top of rail to top of terminal block. |                                     |                           |              |                     |                                     |                           |              |                     |                                   |            |                           |
|   | Single-circuit mini terminal block. |                           |              |                     | Single-circuit mini terminal block. |                           |              |                     | Two-circuit mini terminal block.  |            |                           |
| Specifications  |                                     |                           |              |                     |                                     |                           |              |                     |                                   |            |                           |
| Certifications  |                                     |                           |              |                     |                                     |                           |              |                     |                                   |            |                           |
| Voltage Rating  | 300V AC/DC                          | 500V AC/DC                | 300V AC/DC   | 420V AC/DC          | 300V AC/DC                          | 500V AC/DC                | 300V AC/DC   | 420V AC/DC          | 300V AC/DC                        | 300V AC/DC | 500V AC/DC                |
| Maximum Current   | 15 A                                | 24 A                      | 15 A         | 24 A                | 20 A                                | 32 A                      | 20 A         | 32 A                | 15 A                              | 15 A       | 17.5 A                    |
| Wire Range (Rated Cross Section)  | #30...14 AWG                        | 0.5...2.5 mm <sup>2</sup> | #22...14 AWG | 2.5 mm <sup>2</sup> | #22...12 AWG                        | 0.5...4.0 mm <sup>2</sup> | #22...12 AWG | 4.0 mm <sup>2</sup> | #22...16 AWG                      |            | 0.5...1.5 mm <sup>2</sup> |
| Wire Strip Length   | 0.24 in. (6 mm)                     |                           |              |                     | 0.39 in. (10 mm)                    |                           |              |                     | 0.35 in. (9 mm)                   |            |                           |
| Recommended Tightening Torque   | 4.2...4.6 lb•in (0.47...0.52 N•m)   |                           |              |                     | 4.7...6.2 lb•in (0.53...0.70 N•m)   |                           |              |                     | 4.2...4.6 lb•in (0.47...0.52 N•m) |            |                           |
| Density   | 61 pcs/ft (200/m)                   |                           |              |                     | 50 pcs/ft (166/m)                   |                           |              |                     | 61 pcs/ft (200/m)                 |            |                           |
| Housing Temperature Range   | -40...+195 °F (-40...+90 °C)        |                           |              |                     | -40...+195 °F (-40...+90 °C)        |                           |              |                     | -40...+195 °F (-40...+90 °C)      |            |                           |

|   | 1492-WMG3                                     |  | 1492-WMG4                                     |  |                           |
|---|---|--|---|--|---------------------------|
| Dimensions are not intended to be used for manufacturing purposes.<br>Note: Height dimension is measured from top of rail to top of terminal block. |   |  |   |  |                           |
|   | Single-circuit mini grounding terminal block. |  | Single-circuit mini grounding terminal block. |  |                           |
| Specifications  |   |  |   |  |                           |
| Certifications  |   |  |   |  |                           |
| Maximum Current   | Grounding                                     |  | Grounding                                     |  |                           |
| Wire Range (Rated Cross Section)  | #14 AWG (2.5 mm <sup>2</sup> )                |  | #22...12 AWG                                  |  | 0.5...4.0 mm <sup>2</sup> |
| Wire Strip Length   | 0.31 in. (8 mm)                               |  | 0.39 in. (10 mm)                              |  |                           |
| Recommended Tightening Torque   | 6.2 lb•in (0.7 N•m)                           |  | 5.3 lb•in (0.6 N•m)                           |  |                           |
| Density   | 50 pcs/ft (166 pcs/m)                         |  | 50 pcs/ft (166 pcs/m)                         |  |                           |
| Housing Temperature Range   | —   |  | -40...+195 °F (-40...+90 °C)                  |  |                           |

|   | 1492-J3                         |              |                     |                                    | 1492-J4                       |              |                   |                                  | 1492-J6                       |                   |                                  |            |
|---|---------------------------------|--------------|---------------------|------------------------------------|-------------------------------|--------------|-------------------|----------------------------------|-------------------------------|-------------------|----------------------------------|------------|
| Dimensions are not intended to be used for manufacturing purposes.<br>Note: Height dimension is measured from top of rail to top of terminal block. |                                 |              |                     |                                    |                               |              |                   |                                  |                               |                   |                                  |            |
|   | Feed-through terminal block     |              |                     |                                    | Feed-through terminal block   |              |                   |                                  | Feed-through terminal block   |                   |                                  |            |
| Specifications  |                                 |              |                     |                                    |                               |              |                   |                                  |                               |                   |                                  |            |
| Certifications  |                                 |              |                     |                                    |                               |              |                   |                                  |                               |                   |                                  |            |
| Voltage Rating  | 600V AC/DC                      |              | 800V AC/DC          | 550V AC/DC                         | 600V AC/DC                    |              | 800V AC/DC        | 690V AC/DC                       | 600V AC/DC                    |                   | 800V AC/DC                       | 550V AC/DC |
| Maximum Current   | 25 A                            | 20 A         | 24 A                | 21 A                               | 35 A                          | 25 A         | 32 A              | 28 A                             | 50 A                          | 41 A              | 36 A                             |            |
| Wire Range (Rated Cross Section)  | #28...12 AWG                    | #26...12 AWG | 2.5 mm <sup>2</sup> | 2.5 mm <sup>2</sup> (#20...14 AWG) | #22...10 AWG                  | #26...10 AWG | 4 mm <sup>2</sup> | 4 mm <sup>2</sup> (#20...12 AWG) | #22...8 AWG                   | 6 mm <sup>2</sup> | 6 mm <sup>2</sup> (#20...10 AWG) |            |
| Wire Strip Length   | 0.39 in. (10 mm)                |              |                     |                                    | 0.39 in. (10 mm)              |              |                   |                                  | 0.47 in. (12 mm)              |                   |                                  |            |
| Recommended Tightening Torque   | 4.5...7.1 lb•in (0.5...0.8 N•m) |              |                     |                                    | 9.0 lb•in (1.0 N•m)           |              |                   |                                  | 14.2 lb•in (1.6 N•m)          |                   |                                  |            |
| Density   | 59 pcs/ft (196 pcs/m)           |              |                     |                                    | 49 pcs/ft (163 pcs/m)         |              |                   |                                  | 37 pcs/ft (123 pcs/m)         |                   |                                  |            |
| Housing Temperature Range   | -58...+248 °F (-50...+120 °C)   |              |                     |                                    | -58...+248 °F (-50...+120 °C) |              |                   |                                  | -58...+248 °F (-50...+120 °C) |                   |                                  |            |