

# ZP34K6E-PFV

HFC, R-410A, 60 Hz, 1 - Phase, 208/230 V

Air Conditioning

**Production Status:** Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

## Summary

Performance		
Evaporator Temp. (°F)	45	50
Condensing Temp. (°F)	130	100
Return Gas Temp. (°F)	65	70
Liquid Temp. (°F)	115	85
Capacity (BTU/hr)	34600	46500
Power (W):	3240	2160
Current (Amps):	14.4	9.7
EER(BTU/Wh):	10.7	21.5
Mass Flow (lbs/hr):	506	569
Sound Data @ 50 / 115		
Sound Power (dBA):	68 Avg	73 Max
Vibration mils(peak-peak):	2.0 Avg	3.0 Max
Record Date:	2017-04-18	
Mechanical		
Displacement (in <sup>3</sup> /Rev):	1.95	
Displacement (ft <sup>3</sup> /Hr):		
Overall Length (in):	9.56	
Overall Width (in):	9.56	
Overall Height (in):	16.94	
Mounting Length (in):	7.50	
Mounting Width (in):	7.50	

<b>Mounting Height (in):</b>	17.17
<b>Suction Size (in),Type:</b>	7 / 8 Stub
<b>Discharge Size (in),Type:</b>	1 / 2 Stub
<b>Initial Oil Charge (oz):</b>	42
<b>Oil Recharge (oz):</b>	36
<b>Net Weight (lbs):</b>	74.1
<b>Internal Free Volume (in^3):</b>	196.4

**Horse Power:**

\*Overall compressor height on Copeland Brand Product's specified mounting grommets.

<b>LRA High* (Amps):</b>	109.0
<b>LRA Low*(Amps):</b>	
<b>LRA Half Winding (Amps):</b>	
<b>MCC (Amps):</b>	26
<b>Max Operating Current (Amps):</b>	20.3
<b>RLA, MCC/1.4(use for contactor selection)(Amps):</b>	18.6
<b>RLA, MCC/1.56(use for breaker &amp; wire size selection)(Amps):</b>	16.7
<b>RPM:</b>	3500
<b>Box IP :</b>	21
<b>UL File No:</b>	SA2337
<b>UL File Date:</b>	2003-12-17

\*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

**Capacitors**

Type	Part No	Low MFD	High MFD	Volts	User Description
Run Capacitor	014-0064-25	45.0	0.0	370	
Start Capacitor	014-0061-27	88.0	106.0	330	OPTIONAL

**Alternate Applications**

Refrigerant	Voltage	Phase	Frequency	Application
-------------	---------	-------	-----------	-------------

No data available in table

## Service Parts

Service Parts				
Reference	Component	Quantity	Description	Comment
99	100-0605-02	1	SCREW- TAPTITE W/ LOCKWASHER	
99	527-0116-00	1	SPACER-MOUNTING ASSM	
99	529-0060-24	1	POWER CABLE-MOLDED PLUG	
99	914-0036-03	1	CAP START KIT	
99	914-0037-36	1	RUN CAP KIT	
99	918-0041-00	1	HEATER-CRANKCASE	240V 40W WRAP AROUND
99	918-0041-01	1	HEATER-CRANKCASE	120V 40W WRAP AROUND
99	940-0001-79	1	RELAY-POTENTIAL KIT	
99	943-0120-00	1	SECURE START 1PH SINGLE PACK	
99	971-0066-00	1	MODULE-P210 ASSM	CORESENSE DIAGNOSTICS 2-WIRE

## Accessories

Accessories		
Category	Part Number	Description
CoreSense	971-0066-00	CoreSense™ Diagnostics Module (2-Wire Module, 1-Phase Only)
CoreSense	971-0067-00	CoreSense™ Diagnostics Module (3-Wire Module, 1-Phase Only)
Crankcase Heaters	998-7026-00	Crankcase Heater Enclosure Box
Crankcase Heaters	018-0094-00	Crankcase Heater, 240V, 40W
Crankcase Heaters	018-0094-01	Crankcase Heater, 120V, 40W
Crankcase Heaters	018-0094-03	Crankcase Heater, 480V, 40W, 21.25" Lead Length
Crankcase Heaters	018-0096-00	Crankcase Heater, 240V, 40W, 21.75" Lead Length
Crankcase Heaters	018-0096-01	Crankcase Heater, 120V, 40W, 21.75" Lead Length
Crankcase Heaters	018-0096-02	Crankcase Heater, 480V, 40W, 21.75" Lead Length

Category	Part Number	Description
----------	----------------	-------------

Electrical Components

## Electrical Components

Part No: 071-0546-38

Usage Description: Internal Protector

Vendor Part Number

15HM1987

Vendor Name

SENSATA

Part No: 071-0640-11

Usage Description: Internal Protector

Vendor Part Number

UP5RY0515C01

Vendor Name

UBUKATA

Part No: 071-0640-20

Usage Description: Internal Protector

Vendor Part Number

UP5NY0315-C01

Vendor Name

UBUKATA

### Stator

Part No: 846-5022-22

Usage Description: Stator

Resistance: +/-7%

Start Wdg: 1.61

Run Wdg: 0.61

### Potential

Part No: 040-0166-37

Usage Description: Potential Relay

Vendor Part Number

RVA2AE6D-946

Vendor Name

ELECTRICA

### Run Capacitor

Part No: 014-0064-25

Low MFD: 45.0

Type:Run Capacitor

High MFD: 0.0

### Stator

Part No: 546-5022-22

Usage Description: Stator

Resistance: +/-7%

Start Wdg: 1.61

Run Wdg: 0.61

### Stator

Part No: 846-5125-02

Usage Description: Stator

Resistance: +/-7%

Start Wdg: 1.64

Run Wdg: 0.67

### Start Capacitor

Part No: 014-0061-27

Low MFD: 88.0

Type:Start Capacitor

High MFD: 106.0

Usage Description: Start Capacitor

Volts: 330

Usage Description: Run Capacitor

Volts: 370

## Nomenclature

ZP34K6E-PFV

### Family Series

**Z:** Scroll

### Application Range

**P:** A/C - R-410A/B

### Capacity

**34K:** Capacity Multiplier-1000

### Model Variation

**6:** Model Variation

### Oil Type

**E:** Polyol Ester

### Motor Type

**P:** 1 Phase/Capacitor Run, Permanent Split Capacitor

### Motor Protection

**F:** Internal Inherent Protection

### Voltage

**V:** 60Hz (208/230-1) 50Hz (-)

## Miscellaneous

### Alternate Application

Refrigerant	Freq	Phase	Voltage	Application
-------------	------	-------	---------	-------------

No data available in table

### Nomenclature

[ZP34K6E-PFV](#)

Date	Data Group	Field	Old Data	New Data
08-Apr-2014	Status	Status	P	A
25-Mar-2014	Status	Status	A	P
25-Mar-2014	RatingRefNo	RatingRefNo	13-209	14-10
08-Apr-2014	Rating	PubCode		Y
25-Mar-2014	Rating	PubCode		PRE

<b>Date</b>	<b>Data Group</b>	<b>Field</b>	<b>Old Data</b>	<b>New Data</b>
06-Mar-2013	Rating	PubCode		N
04-Dec-2013	Mech	Rech Oil Charge	38	36
02-Feb-2015	Elec	Max OpCur	18.2	
17-Mar-2014	Elec	Hi LRA	NA	109.0