

ZR32K5E-PFV

HFC, R-407C, 60 Hz, 1 - Phase, 208/230 V

Air Conditioning

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Summary

Performance		
Evaporator Temp. (°F)	45	50
Condensing Temp. (°F)	130	100
Return Gas Temp. (°F)	65	70
Liquid Temp. (°F)	115	85
Capacity (BTU/hr)	31300	42200
Power (W):	2990	1980
Current (Amps):	13.1	9
EER(BTU/Wh):	10.5	21.3
Mass Flow (lbs/hr):	456	520
Sound Data @ 45 / 130		
Sound Power (dBA):	68 Avg	73 Max
Vibration mils(peak-peak):	2.0 Avg	3.0 Max
Record Date:	2015-10-12	
Mechanical		
Displacement (in ³ /Rev):	2.69	
Displacement (ft ³ /Hr):		
Overall Length (in):	9.50	
Overall Width (in):	9.50	
Overall Height (in):	15.86	
Mounting Length (in):	7.50	
Mounting Width (in):	7.50	

Mounting Height (in):	16.08
Suction Size (in),Type:	3 / 4 Stub
Discharge Size (in),Type:	1 / 2 Stub
Initial Oil Charge (oz):	25
Oil Recharge (oz):	19
Net Weight (lbs):	49.9
Internal Free Volume (in^3):	115

Horse Power:

*Overall compressor height on Copeland Brand Product's specified mounting grommets.

LRA High* (Amps):	87.0
LRA Low*(Amps):	
LRA Half Winding (Amps):	
MCC (Amps):	24
Max Operating Current (Amps):	22.5
RLA, MCC/1.4(use for contactor selection)(Amps):	17.1
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	15.4
RPM:	3500
Box IP :	21
UL File No:	SA-2337
UL File Date:	2009-11-19

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Capacitors

Type	Part No	Low MFD	High MFD	Volts	User Description
Run Capacitor	014-0064-29	50.0	0.0	370	
Start Capacitor	014-0061-27	88.0	106.0	330	OPTIONAL

Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
-------------	---------	-------	-----------	-------------

No data available in table

Service Parts

Service Parts				
Reference	Component	Quantity	Description	Comment
1	918-0052-00	1	CRANKCASE HEATER KIT	240V 40W WRAP AROUND
1	918-0052-01	1	CRANKCASE HEATER KIT	120V 40W WRAP AROUND
2	527-0044-15	1	SPACER - MOUNTING ASSM	
5	914-0037-40	1	RUN CAP KIT	
14	529-0060-24	1	POWER CABLE-MOLDED PLUG	

Accessories

Accessories		
Category	Part Number	Description
Crankcase Heaters	018-0094-00	Crankcase Heater, 240V, 40W
Crankcase Heaters	018-0094-01	Crankcase Heater, 120V, 40W
Crankcase Heaters	018-0094-03	Crankcase Heater, 480V, 40W, 21.25" Lead Length
Crankcase Heaters	018-0094-04	Crankcase Heater, 575V, 40W, 21.25" Lead Length
Crankcase Heaters	018-0094-00	Crankcase Heater, 240V, 40W
Crankcase Heaters	018-0094-01	Crankcase Heater, 120V, 40W
Crankcase Heaters	018-0094-04	Crankcase Heater, 575V, 40W, 21.25" Lead Length

Electrical Components

Electrical Components	
Potential	Start Capacitor
Part No: 040-0166-37	Part No: 014-0061-27
Usage Description: Potential Relay	Low MFD: 88.0
<u>Vendor Part Number</u>	Type:Start Capacitor
RVA2AE6D-946	High MFD: 106.0
<u>Vendor Name</u>	Usage Description: Start Capacitor
ELECTRICA	Volts: 330

Run Capacitor

Part No: 014-0064-29

Low MFD: 50.0

Type:Run Capacitor

High MFD: 0.0

Usage Description: Run Capacitor

Volts: 370

Part No: 071-0512-27

Usage Description: Internal Protector

Vendor Part Number

15HM2452

Vendor Name

SENSATA

Stator

Part No: 546-5016-08

Usage Description: Stator

Resistance: +/-7%

Start Wdg: 1.20

Run Wdg: 0.83

Nomenclature

ZR32K5E-PFV

Family Series

Z: Scroll

Application Range

R: A/C - R-22/407C/134a

Capacity

32K: Capacity Multiplier-1000

Oil Type

E: Polyol Ester

Motor Type

P: 1 Phase/Capacitor Run, Permanent Split Capacitor

Motor Protection

F: Internal Inherent Protection

Voltage

V: 60Hz (208/230-1) 50Hz (-)

Miscellaneous

Alternate Application

Refrigerant	Freq	Phase	Voltage	Application
HCFC R-22	60	1 Ø	208/230 V	R1

Nomenclature

[ZR32K5E-PFV](#)

Date	Data Group	Field	Old Data	New Data
12-Oct-2015	Rating	PubCode		Y
12-May-2010	Rating	PubCode	PRE	Y
16-Mar-2010	Rating	PubCode		PRE
17-Nov-2010	2 Pt Perf	Amp Cond 1	9	13.1
17-Nov-2010	2 Pt Perf	Amp Cond 2	13.1	9
17-Nov-2010	2 Pt Perf	Cap Cond 1	42200	31300
17-Nov-2010	2 Pt Perf	Cap Cond 2	31300	42200
17-Nov-2010	2 Pt Perf	EER Cond 1	21.3	10.5
17-Nov-2010	2 Pt Perf	EER Cond 2	10.5	21.3
17-Nov-2010	2 Pt Perf	MassFlow Cond 1	520	456