

ZPS60K5E-PFV

HFC, R-410A, 60 Hz, 1 - Phase, 208/230 V

Air Conditioning

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Summary

Performance		
Evaporator Temp. (°F)	45	50
Condensing Temp. (°F)	130	115
Return Gas Temp. (°F)	65	70
Liquid Temp. (°F)	115	100
Capacity (BTU/hr)	60900	74900
Power (W):	5740	4720
Current (Amps):	27.4	23.2
EER(BTU/Wh):	10.6	15.85
Mass Flow (lbs/hr):	897	997
Sound Data @ 45 / 130		
Sound Power (dBA):	72 Avg	77 Max
Vibration mils(peak-peak):	2.0 Avg	3.0 Max
Record Date:	2017-03-22	
Mechanical		
Displacement (in ³ /Rev):	3.40	
Displacement (ft ³ /Hr):	412.6	
Overall Length (in):	9.48	
Overall Width (in):	9.71	
Overall Height (in):	17.35	
Mounting Length (in):	7.50	
Mounting Width (in):	7.50	

Mounting Height (in):	18.16
Suction Size (in),Type:	7 / 8 Stub
Discharge Size (in),Type:	1 / 2 Stub
Initial Oil Charge (oz):	42
Oil Recharge (oz):	36
Net Weight (lbs):	77.1
Internal Free Volume (in³):	194.7

Horse Power:

*Overall compressor height on Copeland Brand Product's specified mounting grommets.

LRA High* (Amps):	179.2
LRA Low*(Amps):	
LRA Half Winding (Amps):	
MCC (Amps):	46.3
Max Operating Current (Amps):	43.0
RLA, MCC/1.4(use for contactor selection)(Amps):	33.1
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	29.7
RPM:	3500
Box IP :	21
UL File No:	SA2337
UL File Date:	2003-12-17

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Capacitors

Type	Part No	Low MFD	High MFD	Volts	User Description
Run Capacitor	014-0064-14	40.0	0.0	440	
Start Capacitor	014-0053-38	43.0	52.0	330	

Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
R-410A HFC	208/230	1	60	A/C, 67% Load Of Compressor Model

Service Parts

Service Parts				
Reference	Component	Quantity	Description	Comment
1	914-0037-18	1	RUN CAP KIT W/CLAMP	
2	914-0053-07	1	CAP START KIT	
4	527-0116-00	1	SPACER- MOUNTING ASSM	
5	918-0041-00	1	HEATER- CRANKCASE	240V 40W WRAP AROUND
5	918-0041-01	1	HEATER- CRANKCASE	120V 40W WRAP AROUND
5	918-0041-02	1	HEATER- CRANKCASE	480V 40W WRAP AROUND
6	529-0060-24	1	POWER CABLE- MOLDED PLUG	3-PIN MOLDED PLUG
6	529-0138-01	1	CABLE-POWER ASSM	2-PIN MODULATION PLUG
99	940-0140-03	1	RELAY-QUICK CONNECT KIT	
99	998-0069-01	1	ADAPTER & SEAL KIT	

Accessories

Accessories		
Category	Part Number	Description
Crankcase Heaters	018-0095-00	Crankcase Heater, 240V, 70W, 21" Lead Length
Crankcase Heaters	018-0096-06	Crankcase Heater, 240V, 40W, 31.75" Lead Length
Crankcase Heaters	018-0096-05	Crankcase Heater, 480V, 40W, 48.25" Lead Length
Crankcase Heaters	018-0096-04	Crankcase Heater, 240V, 40W, 48.25" Lead Length

Category	Part Number	Description
Crankcase Heaters	018-0096-03	Crankcase Heater, 575V, 40W, 21.75" Lead Length
Crankcase Heaters	018-0096-02	Crankcase Heater, 480V, 40W, 21.75" Lead Length
Crankcase Heaters	018-0096-00	Crankcase Heater, 240V, 40W, 21.75" Lead Length
Crankcase Heaters	018-0095-09	Crankcase Heater, 277V, 70W, 21" Lead Length
Crankcase Heaters	018-0096-01	Crankcase Heater, 120V, 40W, 21.75" Lead Length

Electrical Components

Electrical Components	
Part No: 071-0510-26	Stator
Usage Description: Internal Protector	Part No: 546-5022-10
<u>Vendor Part Number</u>	Usage Description: Stator
16HM153	Resistance: +/-7%
<u>Vendor Name</u>	Start Wdg: 1.91
SENSATA	Run Wdg: 0.36
Potential	Start Capacitor
Part No: 040-0166-02	Part No: 014-0053-38
Usage Description: Potential Relay	Low MFD: 43.0
<u>Vendor Part Number</u>	Type:Start Capacitor
RVA4AG6D-934	High MFD: 52.0
<u>Vendor Name</u>	Usage Description: Start Capacitor
ELECTRICA	Volts: 330
Run Capacitor	
Part No: 014-0064-14	
Low MFD: 40.0	
Type:Run Capacitor	
High MFD: 0.0	
Usage Description: Run Capacitor	
Volts: 440	

Nomenclature

ZPS60K5E-PFV

Family Series

Z: Scroll

Application Range

P: A/C - R-410A/B

Modulation

S: Two Step

Capacity

60K: Capacity Multiplier-1000

Oil Type

E: Polyol Ester

Motor Type

P: 1 Phase/Capacitor Run, Permanent Split Capacitor

Motor Protection

F: Internal Inherent Protection

Voltage

V: 60Hz (208/230-1) 50Hz (-)

Miscellaneous

Alternate Application

Refrigerant	Freq	Phase	Voltage	Application
HFC R-410A	60	1 Ø	208/230 V	R1 A6

Nomenclature

[ZPS60K5E-PFV](#)

Date	Data Group	Field	Old Data	New Data
08-Jul-2011	Status	Status	P	A
08-Jul-2011	Status	Status	P	A
04-Jun-2012	RatingRefNo	RatingRefNo	11-29	12-707
04-Jun-2012	RatingRefNo	RatingRefNo	11-30	12-708
16-Dec-2015	Rating	PubCode		Y
31-May-2012	Rating	PubCode	N	Y
31-Jan-2011	Rating	PubCode		PRE
27-May-2016	2 Pt Perf	Amp Cond 1	23.2	27.4

Date	Data Group	Field	Old Data	New Data
27-May-2016	2 Pt Perf	Amp Cond 2	27.4	23.2