

## Pull-out Disconnect Switches

### Product

DiversiTech Pull-out Disconnect Switches: DDS-30, DDS-60 (fusible), DDS-60U and EDS-60U (non-fusible)

### Application

HVAC circuitry

### Power Rating

30A (DDS-30) or 60A at 240VAC, 10 horsepower max

### Indoor/Outdoor

Indoor/Outdoor

### Package Medium

Metal case with 180 degree opening door

### Advantages

Convenient design allows for easy access to controls via wide-opening, reversible door with full dead front. Fused models benefit from having fuses located in easy pull-out handle with indicator lights for blown fuses. Line, load, and ground terminals aligned for easy wiring. EDS-60U Low-profile model also available for tighter spaces.

### Directions

Please refer to an electronic copy of this product's brochure at [www.diversitech.com/literature/lit-fly-disc.pdf](http://www.diversitech.com/literature/lit-fly-disc.pdf)

### HAZMAT Hazard

None.

### SKU Specific Package Metrics

#### UPC

DDS-30 - 095247082445  
 DDS-60 - 095247082452  
 DDS-60U - 095247082421  
 EDS-60U - 095247089420

#### Unit Dimensions

DDS-30 - 2-5/8"L x 5"W x 7-1/2"H  
 DDS-60 - 2-3/4"L x 5-1/8"W x 8-5/8"H  
 DDS-60U - 2-3/8"L x 5"W x 7-1/2"H  
 EDS-60U - 2-1/2"L x 4.8"W x 6.3"H

#### Unit Weight

DDS-30 - 2.7 lbs.  
 DDS-60 - 3.3 lbs.  
 DDS-60U - 2.5 lbs.  
 EDS-60U - N/A

#### Quantity per Package

10

#### Case Dimensions

DDS-30 - 14"L x 11"W x 8-1/4"H  
 DDS-60 - 16"L x 11"W x 9-1/4"H  
 DDS-60U - 13"L x 11"W x 8-1/4"H  
 EDS-60U - N/A

#### Case Weight

DDS-30 - 28.6 lbs.  
 DDS-60 - 33.7 lbs.  
 DDS-60U - 26.6 lbs.  
 EDS-60U - N/A

#### Accepts Fuse

DDS-30 - Two with 14.5 mm diam x 51.0 length  
 DDS-60 - Two with 20.5 mm x 76.5 mm length  
 DDS-60U - n/a  
 EDS-60U - n/a



DDS-30



DDS-60