

RACEWAY FITTINGS

TILT-IN CABLE BOX CONNECTORS - STEEL



Connects Romex® Brand SIMpull® Type NM-B Cable or non-metallic sheathed cable to box or enclosure

SPECIFICATIONS:

- Material: Steel, Zinc Electroplated
- Notes: Locknut not required

STOCK #	TRADE SIZE	INNER QTY	MASTER QTY
L-15	1/2"	100	500
L-16	3/4"	50	250
L-17	1-1/4"	25	125
L-18	1-1/2"	N/A	25

EZ-IN™ MINI-SPLIT CONNECTORS

64235201



64275801



APPLICATION

- Suitable for use with Ultra-Whip Wiring Assemblies
- Easy and hassle-free fitting hook-ups
- Commonly used for connecting air conditioners, pumps, motors, compressors, pool equipment and similar equipment
- Highly Flexible Non-metallic Conduit with Factory Installed Conductors Type B (LFNC-B) Fittings

SPECIFICATIONS:

The fittings meet UL Standard 514B, CSA Standard C22.2 No.18, and NEMA FB-1. Assemblies complies with NEC® Article 356, UL Standard 1660, and CSA Standard C22.2 No 227.2

STOCK #	TYPE	HUB SIZE	RANGE OVER JACKET OD MIN-MAX	GROMMET COLOR	A LENGTH	B DIAMETER	C HEX	D LENGTH	BOX PACK
64235201	STRAIGHT CONNECTOR, 1/2" STEEL ZINC PLATED TECK50	1/2"	.610 - .720 .560 - .610 .485 - .585"	Black, Grey, Yellow	1-31/32"	1-3/16"	1-1/8"	19/32"	25
64275801	90 DEGREE CONNECTOR TECK5090	1/2"	.610 - .720 .560 - .610 .485 - .585"	Black, Grey, Yellow	3-1/2"	2"	1-1/8"	19/32"	15

NONMETALLIC LIQUID-TIGHT BOX CONNECTORS STRAIGHT



Connects liquid-tight nonmetallic conduit to box or enclosure

SPECIFICATIONS:

- Material: Nylon
- Features: Suitable for use with liquid-tight
- flexible non-metallic conduit, Type B
- Notes: S suffix denotes one-piece screw-in type

STOCK #	TRADE SIZE	INNER QTY	MASTER QTY
NMLQ-1050	1/2"	25	100
NMLQ-1075	3/4"	10	100
NMLQ-1050-S	1/2"	25	100
NMLQ-1075-S	3/4"	25	100

COMPONENTS | RACEWAY FITTINGS